

RATERMANN

MANUFACTURING, INC.

ALUMINUM PORTABLE *for* LPG



SPECIFICATIONS

MODEL/SIZE (LBS.)	6	10	20	30	40
HEIGHT (IN.)	22.1	15.9	20.2	26.1	32.1
HEIGHT (MM)	561	403.8	513	663	814
LPG CAPACITY (GAL)	1.4	2.4	4.7	7.1	9.4
LPG CAPACITY (LITER)	5.3	9	17.8	26.8	35.7
WATER CAPACITY (LBS.)	15	24	48	72	96
WATER CAPACITY (KG.)	6.8	10.8	21.7	32.7	43.5
NOMINAL TARE WEIGHT (LBS.)	8.1	9.7	14.2	16.2	20.9
NOMINAL TARE WEIGHT (KG)	3.7	4.4	6.4	7.3	9.5
CYLINDER DIAMETER (IN.)	6.3	10.3	12.3	12.3	12.3
CYLINDER DIAMETER (MM)	160	261	312	312	312
CYLINDER VOLUME (CU. IN.)	415	664	1,329	1,993	2,657
CYLINDER VOLUME (LITER)	6.8	10.8	21.7	32.7	43.5
COLLAR DIAMETER (IN.)	5.7	7.9	7.9	7.9	7.9
COLLAR DIAMETER (MM)	144.8	200	200	200	200
COLLAR HEIGHT (IN.)	6.5	5.5	5.5	5.5	5.5
COLLAR HEIGHT (MM)	165	140	140	140	140
FOOTRING DIAMETER (IN.)	6.2	8	8	8	8
FOOTRING DIAMETER (MM)	158	230	230	230	230
HORIZONTAL	N/A	Available	Available	Available	Available
STANDARD SPECIFICATION	DOT-4E-260	DOT-4E-240	DOT-4E-240	DOT-4E-240	DOT-4E-240
PART NUMBER	LPGCYL-PA-6	LPGCYL-PA-10	LPGCYL-PA-20	LPGCYL-PA-30	LPGCYL-PA-40

All dimensions are approximate.